

SAFETY DATA SHEET

Clipper Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Clipper Spray

Unique formula identifier (UFI)

DVVP-Y6QK-Y67X-Y2W3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial purposes

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 24	Lubricants, Greases and Release Products
Process category	Description
PROC 19	Hand-mixing with intimate contact and only PPE available
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Eickemeyer

Elastrasse 8

DE - 78532 Tuttlingen

+49 7461 96 580 0

www.eickemeyer.de

E-mail

info@eickemeyer.de

Revision

07/05/2025

SDS Version

2.0

Date of previous version

16/10/2023 (1.0)

1.4. ▼Emergency telephone number

In urgent situations: Call 112 and request the poison information centre. (24h service)

Giftnotrufzentrale Berlin, Emergency telephone: +49 30 19240 (day and night)

See also section 4 for first aid measures.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. ▼Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.
STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

▼ Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
May cause drowsiness or dizziness. (H336)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

▼ Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)

Response

Call a POISON CENTER/doctor if you feel unwell. (P312)

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with local regulation
(P501)

Hazardous substances

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Additional labelling

UFI: DVVP-Y6QK-Y67X-Y2W3

2.3. Other hazards

▼ Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the
criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS No.: EC No.: 919-857-5 REACH: 01-2119463258-33-XXXX Index No.:	60-80%	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	
ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2120063206-63-XXXX Index No.: 603-002-00-5	10-15%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	
carbon dioxide	CAS No.: 124-38-9 EC No.: 204-696-9 REACH: Index No.:	3-5%	Press. Gas (Liq.) , H280	[1]
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	1-3%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. ▼Advice for firefighters

To avoid contact with the substance, wear self-contained breathing apparatus and protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.



6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.
Joint storage is permitted for products in storage classes: 2B, 3, 6.1A, 6.1B, 6.1C, 6.1D, 8A, 8B, 10, 11, 12, 13
Restrictions apply to joint storage of products in storage class: 5.1C
Joint storage is NOT allowed for products in all other storage classes.

Recommended storage material

Always store in containers of the same material as the original container.

Storage class

Storage class 2 B (Aerosol packages).
TRGS 510 - Storage of hazardous substances in non-stationary containers.

Storage conditions

> 0°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼Control parameters

ethanol

Long term exposure limit (8 hours) (ppm): 200
Long term exposure limit (8 hours) (mg/m³): 380
Short term exposure limit (15 minutes) (ppm): 800
Short term exposure limit (15 minutes) (mg/m³): 1520

Category for short-term values: II

Annotations:

DFG = Senate Commission for the examination of Harmful working materials of the DFG (MAK Commission)
Y = No risk of fetal damage is to be feared if the occupational exposure limit (OEL) value and the biological limit value (BLV) are adhered to.

carbon dioxide

Long term exposure limit (8 hours) (ppm): 5000
Long term exposure limit (8 hours) (mg/m³): 9100
Short term exposure limit (15 minutes) (ppm): 10000
Short term exposure limit (15 minutes) (mg/m³): 18200

Category for short-term values: II

Annotations:

DFG = Senate Commission for the examination of Harmful working materials of the DFG (MAK Commission)

EU = European Union (The EU has set an exposure limit: Deviations in value and peak limit are possible.)

propan-2-ol;isopropyl alcohol;isopropanol
 Long term exposure limit (8 hours) (ppm): 200
 Long term exposure limit (8 hours) (mg/m³): 500
 Short term exposure limit (15 minutes) (ppm): 400
 Short term exposure limit (15 minutes) (mg/m³): 1000
 Category for short-term values: II

Annotations:

DFG = Senate Commission for the examination of Harmful working materials of the DFG (MAK Commission)
 Y = No risk of fetal damage is to be feared if the occupational exposure limit (OEL) value and the biological limit value (BLV) are adhered to.

Technical requirements for hazardous substances, workplace exposure limits, TRGS 900 (Jan. 2006)

▼ DNEL

ethanol

Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - General population	Dermal	206 mg/kg legemsvægt pr. dag
Long term - Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	343 mg/kg legemsvægt pr. dag
Long term - Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term - Systemic effects - General population	Inhalation	114 mg/m ³
Long term - Systemic effects - General population	Inhalation	114 mg/m ³
Long term - Systemic effects - Workers	Inhalation	950 mg/m ³
Long term - Systemic effects - Workers	Inhalation	380 mg/m ³
Short term - Local effects - General population	Inhalation	950 mg/m ³
Short term - Local effects - General population	Inhalation	950 mg/m ³
Short term - Local effects - Workers	Inhalation	1900 mg/m ³
Short term - Local effects - Workers	Inhalation	1900 mg/m ³
Long term - Systemic effects - General population	Oral	87 mg/kg legemsvægt pr. dag
Long term - Systemic effects - General population	Oral	87 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - General population	Dermal	319mg/kg bw/dag
Long term - Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	888 mg/kg bw/dag
Long term - Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term - Systemic effects - General population	Inhalation	89mg/m3
Long term - Systemic effects - General population	Inhalation	89 mg/m ³
Long term - Systemic effects - Workers	Inhalation	500 mg7m3
Long term - Systemic effects - Workers	Inhalation	500 mg/m ³
Short term - Systemic effects - General population	Inhalation	178 mg/m ³
Short term - Systemic effects - Workers	Inhalation	1000 mg/m ³
Long term - Systemic effects - General population	Oral	26mg/kg bw/dag
Long term - Systemic effects - General population	Oral	26 mg/kg bw/day
Short term - Systemic effects - General population	Oral	51 mg/kg bw/day

PNEC

ethanol

Route of exposure:	Duration of Exposure:	PNEC:

Freshwater	0,96 mg/l
Freshwater	960 µg/L
Freshwater sediment	3,6 mg/kg
Freshwater sediment	3,6 mg/kg
Intermittent release	2,75 mg/l
Intermittent release (freshwater)	2.75 mg/L
Marine water	0,79 mg/l
Marine water	790 µg/L
Marine water sediment	2,9 mg/kg
Marine water sediment	2.9 mg/kg
Predators	380-720 mg/kg
Sewage treatment plant	580 mg/l
Sewage treatment plant	580 mg/L
Soil	0,63 mg/kg
Soil	630 µg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140,9 mg/l
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Freshwater sediment		552 mg/kg
Intermittent release		140,9 mg/l
Intermittent release (freshwater)		140.9 mg/L
Marine water		140,9 mg/l
Marine water		140.9 mg/L
Marine water sediment		552mg/kg
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		251 mg/l
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg
Soil		28 mg/kg

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

▼ Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Normally, personal respiratory equipment is not necessary			
Skin protection	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	
			
Hand protection	Material	Glove thickness (mm)	Breakthrough time (min.)
Nitrile	0,11	> 480	EN374-2, EN374-3, EN388
			
Eye protection	Type	Standards	
No special when used as intended.	-		

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Clear

Odour / Odour threshold

Alcohol odor

▼ pH

No data available.

Density (g/cm³)

0.85

▼ Kinematic viscosity

No data available.

▼ Particle characteristics

No data available.

Phase changes

▼ Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to aerosols.

▼ Boiling point (°C)

No data available.

▼ Vapour pressure

No data available.

▼ Relative vapour density

No data available.

▼ Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

42

Flammability (°C)

The material is ignitable.

▼ Auto-ignition temperature (°C)

No data available.

▼ Lower and upper explosion limit (% v/v)

No data available.

Solubility

▼ Solubility in water

No data available.

▼ n-octanol/water coefficient (LogKow)

No data available.

▼ Solubility in fat (g/L)

No data available.

9.2. Other information

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. ▼ Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	ethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	10470 mg/kg ·

Product/substance	ethanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>17100 mg/kg ·

Product/substance	ethanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	124,7 mg/l ·

Product/substance	carbon dioxide
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	470000 ppm 0,5 h ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
-------------------	---

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 5840 mg/kg ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: 66,1mg/l 4 h ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: 47,5mg/l 8 h ·

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

▼ Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance ethanol
Species: Fish
Duration: 48 hours
Test: LC50
Result: 8150 mg/l ·

Product/substance ethanol
Species: Fish
Duration: 96 hours
Test: LC50
Result: 1100 mg/l ·

Product/substance ethanol
Species: Daphnia
Duration: 48 hours
Test: EC50

Result: 9268-14221 mg/l ·

Product/substance ethanol
 Species: Algae
 Duration: 7 days
 Test: EC0
 Result: 5000 mg/l ·

Product/substance ethanol
 Species: Crustacean
 Duration: 16 hours
 Test: EC0
 Result: 6500 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Species: Algae
 Duration: 8 days
 Test: NOEC
 Result: >1800 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Species: Fish
 Duration: 96 hours
 Test: LC50
 Result: 8970-9280 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Species: Daphnia
 Duration: 24 hours
 Test: EC50
 Result: 9714 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Species: Crustacean
 Duration: 18 hours
 Test: EC10
 Result: 5175 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Species: Crustacean
 Duration: No data available.
 Test: EC50
 Result: >1000mg/l ·

Based on available data, the classification criteria are not met.

12.2. ▼ Persistence and degradability

Product/substance ethanol
 Conclusion: Readily biodegradable

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Result: 95%
 Conclusion: Readily biodegradable
 Test: OECD 301 E

12.3. ▼ Bioaccumulative potential

Product/substance ethanol
 Conclusion: No potential for bioaccumulation

Product/substance carbon dioxide
 LogKow: 0,8300
 Conclusion: No potential for bioaccumulation

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Conclusion: No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. ▼Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. ▼Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

▼EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID UN proper shipping name	14.2 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1L Tunnel restriction code: (D) See below for additional information
IMDG	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1L EmS: F-D S-U See below for additional information
IATA	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information

* Packing group

** Environmental hazards

▼Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection

with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3b - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 5.000 tonnes (net) / (upper-tier): 50.000 tonnes (net)

▼ REACH, Annex XVII

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics is subject to REACH restrictions (entry 40). ethanol is subject to REACH restrictions (entry 40).

propan-2-ol;isopropyl alcohol;isopropanol is subject to REACH restrictions (entry 40).

▼ WGK classification

WGK class: WGK 3

▼ Additional information

Not applicable.

Sources

Law on the protection of mothers at work, in training and in studies (Mutterschutzgesetz - MuSchG) 23.05.2017 (BGBl. I S. 1228).

The Aerosol Packaging Ordinance of September 27, 2002 (BGBl. I p. 3777, 3805), amended with the thirteenth Ordinance on the Product Safety Act (Aerosol Packaging Ordinance) (13th ProdSV) of November 8, 2011 (BGBl. L p. 2178).

Twelfth ordinance for the implementation of the Federal Immission Control Act (Major Accidents Ordinance - 12th BImSchV).

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H280, Contains gas under pressure; may explode if heated.

H304, May be fatal if swallowed and enters airways.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 19 = Hand-mixing with intimate contact and only PPE available

PC 24 = Lubricants, Greases and Release Products

ERC 8a = Wide dispersive indoor use of processing aids in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

▼ Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Lisbet Tetsche

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DE-en