Transducers for Vetus 9

Version: 1.0





Probe	Illustration	Type of Array	Parameters	Application	Biopsy kit
C11-3s		Curved	 Bandwidth: 2.6 – 12.8 MHz Extended FOV: 113° Convex Radius: 15 mm 	Abdomen (Canine, Feline), Reproduction (Canine, Feline), Small Parts (Canine, Feline)	NGB-018, available, multi angle, reusable
SC6-1s	A CONTRACTOR	Curved	 Bandwidth: 1.2 – 6.0 MHz Extended FOV: 72° Convex Radius: 60 mm 	Abdomen (Canine, Equine, Bovine, Ovine, Camel, Alpaca), Reproduction (Canine, Equine, Bovine, Ovine, Camel, Alpaca)	NGB-022, available, multi angle, reusable
L13-3Ns		Linear	 Bandwidth: 3.0 – 13.0 MHz Field of View (max): 38.0 mm 	Abdomen (Canine, Feline), Small Parts (Canine, Feline), Ocular (Canine, Feline), MSK (Equine, Camel)	NGB-053, available, multi-angle, reusable
P8-2s		Phased	 Bandwidth: 2.3 – 8.0 MHz Field of View (max): 90° 	Cardiology (Canine, Feline), Abdomen (Canine, Feline)	None
P10-4s	5101 ·	Phased	 Bandwidth: 3.0 – 11.4 MHz Field of View (max): 90° 	Cardiology (Canine, Feline), Abdomen (Canine, Feline)	None
SP5-1s	1. Same	Phased	 Bandwidth: 1.5 – 4.5 MHz Field of View (max): 90° 	Cardiology (Canine, Equine, Bovine, Ovine, Camel, Alpaca)	NGB-011, available, multi-angle, reusable



